Baleband

For Strapping Systems

General

Our baleband material is responsibly and sustainably sourced, FPC certified fiber product for pulp bale strapping and banding. It is a safer alternative to twisted wire and the dewiring process. This product is based upon our 30+ years' experience in the strapping market. that is engineered with the same high quality control measures in place as our paper band. Each baleband is manufactured under rigorous quality control measures, the same standards that have long defined our paper band products, guaranteeing durability, strength, and dependable performance.

Baleband Product Characteristics

Variables	Units	Test Method	Min	Max	Tested Value
Thickness	Inches	Caliper	0.034	0.046	0.041
Width	Inches	Caliper	0.715	0.755	0.744
Tensile	Pounds	TAPPI 494 om-13	300	N/A	341 Lbs.
Repulpability	Revs	FPI documented procedure	N/A	50,000	50,000

Packing Information

Bleached White

Sold in 18 coils per pallet

4,000' per coil, 6" ID core

Coil Width 8", Diameter 14"

Baleband must be stored in a dry place at room temperature.
Store in a cool, dry place between 68F and 75F (20C-24C) prior to use. Optimal storage conditions: 70F (21C) 50% relative humidity.

83 Peeples Valley Road, Cartersville, GA 30121
770.423.0934 • monarchpapergroup.com